



# Lightning products

## Support mast and fixing

### Chimney strap

The strapping tabs are used to fix all lightning rods with initiation device and simple rods from the DUVAL MESSIEN range equipped with an extension pole or not and on any type of large diameter support such as industrial chimneys, pylon heads , concrete masts, etc. (square or rectangular section).

It is made up of 2 chimney clips and 5 meters of galvanized steel strapping 40 x 0.6mm supplied. The quantity of legs will be determined according to the height of the desired protection.



- 1 lightning rod alone: 2 offset legs
- 1 lightning rod equipped with an extension pole: 2 offset legs \*
- 1 lightning rod equipped with a set of 2 masts: 3 offset legs \*
- 1 lightning rod equipped with a set of 3 masts: 3 offset legs \*

\* This quantity must however be validated according to the installation area, the constraints linked to bad weather and the support. (it is recommended to respect a minimum spacing of 300 to 400mm between legs).

### Characteristics

Reference :	<b>CERCLCHEM</b>
Material :	Galvanized steel (strap) + Dichromated steel (fasteners)
Composition :	2 Fasteners + 5 m of strap
Dimensions :	320 x 110 x 100
Weight (kg) :	1,8
Standards :	NF EN 62561-4 – NF EN 62305-3

**Duval Messien® - A full range of lightning and overvoltage protection.**

**In the continue framework of its products, Duval Messien shall be entitled to modify specifications without notice.**