

DUVAL MESSIEN

A know how famous since more than one century
Technical datasheet



Lightning earthing system maker

In compliance with NF EN 62305-3 standard

It ensures the detection of the lightning conductor's earthing. It can be used as a warning means (prevention of risks of step and contact voltages).

Each down conductor and lightning conductor's earthing must be equipped with this lightning earthing system marker, in the case of a risk of step and contact voltages.

It must be clearly legible at a distance of 3 meters and must be installed at reading height.

Reference:	PLAQDMTEROR2
Type of installation:	Earthing system
Assembly:	Fixing near the down conductor or the metallic structure connected to the earthing system
Use:	Lightning or electrical earthing system
Material:	Aluminum
Dimensions (in mm):	200 x 200 x 200 x 1
Weight (in kg):	0,042
Standards:	NF EN 62305-3 - NFC 17-102



Join us on :



Version 2020 - A

Duval Messien Tel:+33 1 60 18 58 70 / Fax :+33 1 60 18 58 71 – Email : contact@duval-messien.fr
30 rue de la Varenne – 94100 Saint Maur des Fossés – France - Web : www.duval-messien.fr
Agence Ouest (Nantes) Tél :+33 2 40 54 79 30 - Agence Sud Est (Velaux) Tel :+33 4 42 34 71 00