

DUVAL MESSIEN

A know how famous since more than one century
Technical datasheet



Stainless steel coupling

In compliance with NF EN 62561-1 standard

This flat-round coupling is designed to connect the down conductors or meshes by mechanical clamping.

It allows to connect up to 4 tinned copper tape conductors.

27x2mm tinned copper tape Conductors, 30x2mm stainless steel, 30x3mm aluminum, 33,5x3mm galvanized steel, round Ø8 and 10mm are kept under pressure after clamping of 4 inox screws M6 delivered.

It can also be used to connect the equipotential bonding with cable of section 16mm² to 50mm².

Reference:	RACPLTRND
Type of installation:	Lightning rod – meshed cage
Assembly:	Clamping of the conductors with this coupling.
Use:	Interconnections
Material:	Stainless steel
Conductors:	Tape of section 27x2 to 30x2, round Ø8 to 10 mm, cable of section 16 to 50mm ²
Dimensions (in mm):	55 x 55 x 20
Weight (in kg):	0,100
Standards:	NF EN 62561-1 – NF EN 62305-3 – NFC 17102



Join us on :



Version 2020 - A

Duval Messien Tel:+33 1 60 18 58 70 / Fax :+33 1 60 18 58 71 – Email : contact@duval-messien.fr
30 rue de la Varenne – 94100 Saint Maur des Fossés – France - Web : www.duval-messien.fr
Agence Ouest (Nantes) Tél :+33 2 40 54 79 30 - Agence Sud Est (Velaux) Tel :+33 4 42 34 71 00